



APPLICATION DETAILS	
APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM.
RATED TORQUE	- Nm
A.S.F.	-
COUPLING CAPACITY	
COUPLING RATING	0.18KW AT 100RPM.
RATED TORQUE	18 Nm
MAX. BORE TYPE-II	24mm.
WEIGHT (APPROX)	0.14kg
INERTIA (WK ²)	4.3X10 ⁻⁵ kg-m ²
MAX. MISALIGNMENT	
AXIAL	±1.6mm
ANGULAR	0.80°
PARALLE	0.15mm

SR NO	DESCRIPTION	MATERIAL	QTY.
3	HUB-II	ALUMINIUM	1
2	SPIDER	POLYURETHANE (BLUE)	1
1	HUB-II	ALUMINIUM	1

REV.	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

TITLE:	RRJ-19 II/II /-----	MATERIAL:	REFER TABLE	AUTHORITY	INITIALS	SIGN	DATE
CUSTOMER NAME:	-	SCALE:	NTS	REF. No.:			
				RATHI TRANSPower PVT LTD PUNE 411014			
				DRG. No.: R/L-----/-			

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions