



(REF.)

DRIVEN SIDE

APPLICATION DETAILS	
APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM.
RATED TORQUE	- Nm
A.S.F.	-
COUPLING CAPACITY	
COUPLING RATING	3.47KW AT 100RPM.
RATED TORQUE	332Nm
MAX. BORE TYPE-I	40mm
WEIGHT (APPROX)	2.0kg
INERTIA (WK ²)	1.85X10 ⁻³ kg-m ²
MAX. MISALIGNMENT	
AXIAL	±2.2mm
ANGULAR	0.90°
PARALLE	0.25mm

REV/ DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

S/N	SR NO	DESCRIPTION	MATERIAL	QTY.
3	HUB-I	C:1 IS:210		1
2	SPIDER	POLYURETHANE (BLUE)		1
1	HUB-I	C:1 IS:210		1

TITLE: **RRJ-38 I/1 /-/-**
 CPLG.
 CUSTOMER NAME: _____

MATERIAL: **REFER TABLE**

AUTHORITY INITIALS	SIGN	DATE
DRAWN	-	-
CHECKED	-	-
APPROVED	-	-

SCALE: N/S REF. No.: _____

DWG No.: **R/L-/-**

RATHI TRANSPOWER PVT LTD
 PUNE 411006