



**DRIVE SIDE**

**DRIVEN SIDE**

(REF.)

**APPLICATION DETAILS**

APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM.
RATED TORQUE	- Nm
A.S.F.	-

**COUPLING CAPACITY**

COUPLING RATING	3.47KW AT 100RPM.
RATED TORQUE	332Nm
MAX. BORE TYPE-I & II	40 & 48mm
WEIGHT (APPROX)	2.4kg
INERTIA (WK <sup>2</sup> )	2.45X10 <sup>-3</sup> kg-m <sup>2</sup>

**MAX. MISALIGNMENT**

AXIAL	±2.2mm
ANGULAR	0.90°
PARALLE	0.25mm

S/N	SR NO	DESCRIPTION	MATERIAL	QTY.
3	HUB-I	HUB-I	C.I IS:210	1
2	SPIDER	SPIDER	POLYURETHANE (BLUE)	1
1	HUB-I	HUB-I	C.I IS:210	1

TITLE: **RRJ-38 I/II /-----**  
 CPLG.  
 MATERIAL: **REFER TABLE**  
 CUSTOMER NAME: \_\_\_\_\_  
 AUTHORITY INITIALS: \_\_\_\_\_ SIGN: \_\_\_\_\_ DATE: \_\_\_\_\_  
 DRAWN: \_\_\_\_\_ CHECKED: \_\_\_\_\_ APPROVED: \_\_\_\_\_  
 SCALE: N/S REF. No.: \_\_\_\_\_

**RATHI** RATHI TRANSPOWER PVT LTD PUNE 411014  
 DRG No.: \_\_\_\_\_ /-  
 3 EN-F-112

REV. DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

1	2	3	4	5	6	7	8	J	I	H	G	F	E	D	C	B	A