



**APPLICATION DETAILS**

APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM.
RATED TORQUE	- Nm
A.S.F.	-

**COUPLING CAPACITY**

COUPLING RATING	1.9KW AT 100RPM.
RATED TORQUE	182Nm
MAX. BORE TYPE-III	48mm
WEIGHT (APPROX)	3.6kg
INERTIA (WK <sup>2</sup> )	3.72X10 <sup>-3</sup> kg-m <sup>2</sup>

**MAX. MISALIGNMENT**

AXIAL	$\pm 2.2$ mm
ANGULAR	0.90°
PARALLE	0.25mm

3	HUB-I	C.I IS:210	1
2	SPIDER	POLYURETHANE (GRAY)	1
1	HUB-I	C.I IS:210	1
SR NO	DESCRIPTION	MATERIAL	QTY.

REV.	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

TITLE: **RRJ-38 III/III /----**  
**CPLG.**

MATERIAL: **REFER TABLE**

CUSTOMER NAME: -

SCALE: NTS REF. No.: -

**RAHI** RATHI TRANSPOWER PVT LTD PUNE 411014

DRG. No.: -----/-

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions