



APPLICATION DETAILS	
APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM.
RATED TORQUE	- Nm
A.S.F.	-
COUPLING CAPACITY	
COUPLING RATING	4.99KW AT 100RPM.
RATED TORQUE	477 Nm
MAX. BORE TYPE-III	55mm
WEIGHT (APPROX)	5.5kg
INERTIA (WK <sup>2</sup> )	8.54X10 <sup>-3</sup> kg-m <sup>2</sup>
MAX. MISALIGNMENT	
AXIAL	±2.3mm
ANGULAR	0.90°
PARALLE	0.30mm

SR NO	DESCRIPTION	MATERIAL	QTY.
3	HUB-III	C.I. IS:210 FG 260	1
2	SPIDER	POLYURETHANE (BLUE)	1
1	HUB-III	C.I. IS:210 FG 260	1

REV.	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

TITLE: <b>RRJ-42 III/III /-----</b>		MATERIAL: <b>REFER TABLE</b>		AUTHORITY	INITIALS	SIGN	DATE
CPLG.				DRAWN	-	-	-
CUSTOMER NAME: -				CHECKED	-	-	-
				APPROVED	-	-	-
				SCALE: NTS	REF. No.:		
		<b>RATHI TRANSPOWER PVT LTD</b> PUNE 411014		DRG. No.:		-----/-	

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions