



**DRIVE SIDE**

**DRIVEN SIDE**

(REF.)

MSX0.8P TAPPED HOLE  
FOR SET SCREW ON KEYWAY.

**APPLICATION DETAILS**

APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM
RATED TORQUE	- Nm
A.S.F.	-

**COUPLING CAPACITY**

COUPLING RATING	3.1KW AT 100RPM.
RATED TORQUE	296Nm
MAX. BORE TYPE-I	52mm
WEIGHT (APPROX)	4.4kg
INERTIA (WK <sup>2</sup> )	6.2X10 <sup>-3</sup> kg-m <sup>2</sup>

**MAX. MISALIGNMENT**

AXIAL	±3.0mm
ANGULAR	1°
PARALLEL	0.35mm

S/N	SR NO	DESCRIPTION	MATERIAL	QTY.
3	HUB-I	C.I. IS:210 FG 260		1
2	SPIDER	POLYURETHANE (GRAY)		1
1	HUB-I	C.I. IS:210 FG 260		1

TITLE: **RRJ-48 1/1 /- - - - -**  
CPLG. REFER TABLE

CUSTOMER NAME: -

AUTHORITY	INITIALS	SIGN	DATE
DRAWN	-	-	-
CHECKED	-	-	-
APPROVED	-	-	-

SCALE: NTS REF. No.: -  
DRG. No.: - - - - - / -  
**RATHI** RATHI TRANSPOWER PVT LTD  
PUNE 411006

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions