



APPLICATION DETAILS	
APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM.
RATED TORQUE	- Nm
A.S.F.	-
COUPLING CAPACITY	
COUPLING RATING	3.1KW AT 100RPM.
RATED TORQUE	296 Nm
MAX. BORE TYPE-III	62mm
WEIGHT (APPROX)	4.2kg
INERTIA (WK ²)	13.4X10 ⁻³ kg-m ²
MAX. MISALIGNMENT	
AXIAL	±3.0mm
ANGULAR	1°
PARALLE	0.35mm

SR NO	DESCRIPTION	MATERIAL	QTY.
3	HUB-III	C.I. IS:210 FG 260	1
2	SPIDER	POLYURETHANE (GRAY)	1
1	HUB-III	C.I. IS:210 FG 260	1

REV.	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

TITLE:	RRJ-48 III/III /----	MATERIAL:	REFER TABLE	AUTHORITY	INITIALS	SIGN	DATE
CUSTOMER NAME:	-	SCALE:	NTS	REF. No.:			
				RATHI TRANSPOR PVT LTD		DRG. No.:	
PUNE 411014				-----/-			

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions