



APPLICATION DETAILS	
APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM
RATED TORQUE	- kNm
A.S.F	-
COUPLING SPECIFICATIONS	
COUPLING RATING	0.221 kW @ 100 RPM
RATED TORQUE	21.1 Nm
MAX BORE	28 mm
WEIGHT (APPROX)	1.56 Kg
INERTIA WK ² (APPROX)	0.003 Kgm ²
CPLG COMPONENTS DYNAMICALLY BALANCED TO GR.6.3 AS PER ISO 1940- I.	
MAXIMUM MISALIGNMENTS	
AXIAL DEFLECTION	±1.0 mm
ANGUALR DEFLECTION	1°
RADIAL DEFLECTION	0.4 mm

ITEM NO.	DESCRIPTION	MATERIAL	QTY.
7	COUPLING BOLT	HIGH TENSILE STEEL	6
6	SPRING WASHER	SPRING STEEL	6
5	JAW BODY-2	C.I. IS 210 GR. FG 260	1
4	JAW BODY-1	C.I. IS 210 GR. FG 260	1
3	SPIDER	NITRILE RUBBER	1
2	HUB DRIVEN SIDE	C.I. IS 210 GR. FG 260	1
1	HUB DRIVE SIDE	C.I. IS 210 GR. FG 260	1

REV.	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

TITLE: **RRL-95(75)/- CPLG** MATERIAL: **REFER TABLE**

CUSTOMER NAME: -

SCALE: 1:1 REF. No.: -

RATHI RATHI TRANSPOWER PVT LTD PUNE 411014 DRG. No.: -

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions