


J I H G F E D C B A



APPLICATION DETAILS	
APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM
RATED TORQUE	- kNm
A.S.F	-
COUPLING SPECIFICATIONS	
COUPLING RATING	0.49 KW AT 100 RPM.
RATED TORQUE	46.4 Nm
MAX.BORE	30 mm.
WEIGHT(Approx.)	2.17 Kg
INERTIA WK <sup>2</sup>	0.00134 Kgm <sup>2</sup>
COUPLING HUBS DYNAMICALLY BALANCED TO GR6.3 AS PER ISO 1940-1.	
MAX. MISALIGNMENTS	
AXIAL DEFLECTION	$\pm 1$ mm
ANGUALR DEFLECTION	1°
RADIAL DEFLECTION	0.4mm

ITEM NO.	DESCRIPTION	MATERIAL	QTY.
6	HUB DRIVEN SIDE	C.I. I.S. 210 GR.FG 260	1
5	CHEESE HEAD SCREW	STAINLESS STEEL	6
4	OUTSIDE RING	C.R.C.A	2
3	SNAP WRAP	NITRILE RUBBER	2
2	SPACER	ALUMINIUM	1
1	HUB DRIVE SIDE	C.I. I.S. 210 GR.FG 260	1

REV.	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE	TITLE: <b>RRS-099 (90)/-CPLG.</b>	MATERIAL: <b>REFER TABLE</b>	AUTHORITY	INITIALS	SIGN	DATE
						CUSTOMER NAME: -		DRAWN	-		-
								CHECKED	-		-
								APPROVED	-		-
								SCALE: NTS	REF. No.:		
						<b>RATHI</b>	<b>RATHI TRANSPOWER PVT LTD</b> PUNE 411014	DRG. No.:			
								---			

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions