



**DRIVE SIDE**

**DRIVEN SIDE**

M6 X 1P  
SET SCREW ON KEYWAY

M6 X 1P  
SET SCREW ON KEYWAY

APPLICATION DETAILS	
APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM
RATED TORQUE	- kNm
A.S.F	-
COUPLING SPECIFICATIONS	
COUPLING RATING	0.73 KW AT 100 RPM.
RATED TORQUE	69.6 Nm
MAX.BORE	30 mm.
WEIGHT(Approx.)	2.17 Kg
INERTIA WK <sup>2</sup>	0.00134 Kgm <sup>2</sup>
COUPLING HUBS DYNAMICALLY BALANCED TO GR6.3 AS PER ISO 1940-1.	
MAX. MISALIGNMENTS	
AXIAL DEFLECTION	±1 mm
ANGUALR DEFLECTION	1°
RADIAL DEFLECTION	0.4mm

ITEM NO.	DESCRIPTION	MATERIAL	QTY.
6	HUB DRIVEN SIDE	C.I. I.S. 210 GR.FG 260	1
5	CHEESE HEAD SCREW	STAINLESS STEEL	6
4	OUTSIDE RING	C.R.C.A	2
3	SNAP WRAP	POLYURETHANE RUBBER	2
2	SPACER	ALUMINIUM	1
1	HUB DRIVE SIDE	C.I. I.S. 210 GR.FG 260	1

REV.	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

TITLE: **RRS-099 (90)/-CPLG.** MATERIAL: **REFER TABLE**

CUSTOMER NAME: -

SCALE: NTS REF. No.: -

**RATHI** RATHI TRANSPower PVT LTD PUNE 411014 DRG. No.: -/-

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions