



APPLICATION DETAILS	
APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM.
RATED TORQUE	- Nm
A.S.F.	-
COUPLING CAPACITY	
COUPLING RATING	5.86KW AT 100RPM.
RATED TORQUE	560 Nm
MAX. BORE TYPE-III	55mm
WEIGHT (APPROX)	5.5kg
INERTIA (WK ²)	8.54X10 ⁻³ kg-m ²
MAX. MISALIGNMENT	
AXIAL	± 2.3 mm
ANGULAR	0.90°
PARALLE	0.30mm

SR NO	DESCRIPTION	MATERIAL	QTY.
3	HUB-III	C.I. IS:210 FG 260	1
2	SPIDER	POLYURETHANE (LIGHT IVORY)	1
1	HUB-III	C.I. IS:210 FG 260	1

REV.	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

TITLE: RRJ-42 III/III /----- CPLG.	MATERIAL: REFER TABLE	AUTHORITY	INITIALS	SIGN	DATE
CUSTOMER NAME: -	SCALE: NTS	REF. No.:			
RATHI TRANSPOWER PVT LTD PUNE 411014		DRG. No.:		-----/-	

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions