



**APPLICATION DETAILS**

APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM
RATED TORQUE	- Nm
A.S.F.	-

**COUPLING CAPACITY**

COUPLING RATING	3.10KW AT 100RPM.
RATED TORQUE	296Nm
MAX. BORE TYPE-I & II	52 & 62mm
WEIGHT (APPROX)	5.2kg
INERTIA (WK <sup>2</sup> )	9.6X10 <sup>-3</sup> kg-m <sup>2</sup>

**MAX. MISALIGNMENT**

AXIAL	$\pm 3.0$ mm
ANGULAR	1°
PARALLEL	0.35mm

Sr No	DESCRIPTION	MATERIAL	QTY.
3	HUB-II	C.I. IS:210 FG 260	1
2	SPIDER	POLYURETHANE (GRAY)	1
1	HUB-I	C.I. IS:210 FG 260	1

TITLE: **RRJ-48 I/II /-----**  
**CPLG.**  
 MATERIAL: **REFER TABLE**  
 CUSTOMER NAME: **-----**  
 APPROVED: **-----**  
 SCALE: NTS REF: No.: **-----**

REV. DWGN NO. DESCRIPTION REV. BY APPD. BY DATE

**RATHI** RATHI TRANSPOWER PVT LTD PUNE 411014 DRG. No.: **-----**