



DRIVE SIDE

DRIVEN SIDE

APPLICATION DETAILS	
APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM
RATED TORQUE	- kNm
A.S.F	-
COUPLING SPECIFICATIONS	
COUPLING RATING	1.2 KW AT 100 RPM.
RATED TORQUE	116 Nm
MAX. BORE	35 mm.
WEIGHT (Approx.)	2.17 Kg
INERTIA WK ²	0.00134 Kgm ²
COUPLING HUBS DYNAMICALLY BALANCED TO GR6.3 AS PER ISO 1940-1.	
MAX. MISALIGNMENTS	
AXIAL DEFLECTION	±1 mm
ANGULAR DEFLECTION	1°
RADIAL DEFLECTION	0.4mm

ITEM NO.	DESCRIPTION	MATERIAL	QTY.
6	HUB DRIVEN SIDE	C.I. I.S. 210 GR.FG 260	1
5	CHEESE HEAD SCREW	STAINLESS STEEL	6
4	OUTSIDE RING	C.R.C.A	2
3	SNAP WRAP	H-Trans	2
2	SPACER	ALUMINIUM	1
1	HUB DRIVE SIDE	C.I. I.S. 210 GR.FG 260	1

REV.	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

TITLE: **RRS-100 (90)/-CPLG.** MATERIAL: **REFER TABLE**

CUSTOMER NAME: -

SCALE: NTS REF. No.: -

DRG. No.: -

RAHI RATHI TRANSPower PVT LTD PUNE 411014

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions