

**APPLICATION DETAILS**

APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM
RATED TORQUE	- Nm
A.S.F.	-

**COUPLING SPECIFICATIONS**

COUPLING RATING	0.1 KW AT 100 RPM
RATED TORQUE	9.80 Nm
MAX. BORE	22 mm
WEIGHT (Approx.)	0.19 Kg
INERTIA (WK <sup>2</sup> )	5.34x10 <sup>-6</sup> Kgm <sup>2</sup>

CPLG. HUBS DYNAMICALLY BALANCED TO GR.6.3 AS PER ISO 21940-11.

**MAX. MISALIGNMENTS**


AXIAL DEFLECTION	±1 mm
ANGULAR DEFLECTION	1°
RADIAL DEFLECTION	0.4 mm

SR NO	DESCRIPTION	MATERIAL	QTY.
1	HUB	LM24	2
2	SPIDER	NITRILE RUBBER	1

TITLE: L-75/-CP1G REFER TABLE

CUSTOMER NAME: CP1G

REV. / CHRN NO.	DESCRIPTION	REV. BY	DATE


**RATHI TRANSPOWER PVT LTD**  
 PUNE 411014  
 DRG. No.: /-  
 3 EN-F-112, REV.1