



**APPLICATION DETAILS**

APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM
RATED TORQUE	- Nm
A.S.F.	-

**COUPLING SPECIFICATIONS**

COUPLING RATING	1.2 KW AT 100 RPM
RATED TORQUE	116 Nm
MAX. BORE	30 mm
WEIGHT (Approx.)	0.75 Kg
INERTIA (WK <sup>2</sup> )	2.88x10 <sup>-5</sup> Kgm <sup>2</sup>

CPLG. HUBS DYNAMICALLY BALANCED TO GR.6.3 AS PER ISO 21940-11.

**MAX. MISALIGNMENTS**

AXIAL DEFLECTION	±1 mm
ANGULAR DEFLECTION	1°
RADIAL DEFLECTION	0.4 mm

57 E/ O/

SR NO	DESCRIPTION	MATERIAL	QTY.
1	HUB	CI GR.FG 260	2
2	SPIDER	H TRANS	1

TITLE: **L-99/-CP1G**  
 CUSTOMER NAME: **CP1G**  
 REFER TABLE

MATERIAL: **REFER TABLE**

DRAWN	-	AUTHORITY	INITIALS	SIGN	DATE
CHECKED	-	APPROVED	-	-	-
SCALE	-	SCALE	-	-	-

DRG. No.: **---**  
 RATHI TRANSPOWER PVT LTD  
 PUNE 411014