



APPLICATION DETAILS	
APPLICATION	-
RATED POWER	-
RATED SPEED	-
RATED TORQUE	-
A.S.F.	-

COUPLING SPECIFICATIONS	
COUPLING RATING	1.5 kW @ 100 RPM
RATED TORQUE	0.14 kNm.
PEAK TORQUE	0.21 kNm.
MAX. SPEED	7200 rpm.
MAX. BORE	PIN HALF 32 mm BUSH HALF 30 mm
WEIGHT (Approx.)	2.47 Kg
INERTIA (MK ²)	0.0037 Kg m ²
COUPLING HUBS DYNAMICALLY BALANCED TO GR. 6.3 AS PER ISO: 21940-11	

MAX. MISALIGNMENTS	
AXIAL DEFLECTION	± 2 mm.
ANGULAR DEFLECTION	1°
RADIAL DEFLECTION	0.3 mm

REV.	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

SERIAL NO.	DESCRIPTION	MATERIAL	QTY
5	NYLOCK NUT	GR. 8	3
4	BUSH	POLYURETHANE	3
3	PIN	EN-8D/15B25	3
2	BUSH HALF	CI IS-210 G.F.G-260	1
1	PIN HALF	CI IS-210 G.F.G-260	1

TITLE:	RB-106-3 /----- CPLG.	MATERIAL:	REFER TABLE
CUSTOMER NAME:		AUTHORITY/INITIALS	SIGN
		DRAWN	DATE
		CHECKED	
		APPROVED	
		SCALE: NTS/REF. No.:	
		DRG. No.:	