



DRIVE END

DRIVEN END

APPLICATION DETAILS	
APPLICATION	-
RATED POWER	-
RATED SPEED	-
RATED TORQUE	-
A.S.F.	-

COUPLING SPECIFICATIONS	
COUPLING RATING	14 kW @ 100 RPM
RATED TORQUE	1.33 kNm.
PEAK TORQUE	2.6 kNm.
MAX. SPEED	4500 rpm.
MAX. BORE	65 mm
MAX. BORE	80 mm
WEIGHT (Approx.)	10.22 Kg
INERTIA (MK ²)	0.0409 Kg ^m ²

REV/	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

S/N	SR NO	DESCRIPTION	MATERIAL	QTY
5	5	NYLOCK NUT	GR. 8	6
4	4	BUSH	H-TRANS	6
3	3	PIN	EN-8D/15B25	6
2	2	BUSH HALF	CI IS-210 G.F.G-260	1
1	1	PIN HALF	CI IS-210 G.F.G-260	1

TITLE:	RB-162-6 /----- CP1G.	MATERIAL:	REFER TABLE
CUSTOMER NAME:	RATHI TRANSPOWER PVT LTD	AUTHORITY/INITIALS	DATE
	PUNE 411014	DRAWN	
		CHECKED	
		APPROVED	
		SCALE: NTS/REF: No.:	
		DRG. No.:	