



APPLICATION DETAILS	
APPLICATION	-
RATED POWER	-
RATED SPEED	-
RATED TORQUE	-
A.S.F.	-

  

COUPLING SPECIFICATIONS	
COUPLING RATING	160 kW @ 100 RPM
RATED TORQUE	15.27 kWhn.
PEAK TORQUE	30.55 kWhn.
MAX. SPEED	2100 rpm.
MAX. BORE	135 mm
PIN HALF	125 mm
BUSH HALF	125 mm
WEIGHT (Approx.)	72.42 Kg
INERTIA (WK <sup>2</sup> )	0.75 Kgmm <sup>2</sup>

  

COUPLING HUBS DYNAMICALLY BALANCED TO GR. 6.3 AS PER ISO: 21940-11

REV.	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

TITLE:	RB-350-12 /----- CPLG.	MATERIAL:	REFER TABLE
CUSTOMER NAME:	RATHI TRANSPOWER PVT LTD	PUNE 411014	DRG. No.: -

  

S/N	SR NO	DESCRIPTION	MATERIAL	QTY
5	5	NYLOCK NUT	GR. 8	12
4	4	BUSH	H TRANS	12
3	3	PIN	EN-80/15B25	12
2	2	BUSH HALF	CI IS-210 G.F.G-260	1
1	1	PIN HALF	CI IS-210 G.F.G-260	1

  

AUTHORITY/INITIALS	SIGN	DATE