



APPLICATION DETAILS	
APPLICATION	-
RATED POWER	-
RATED SPEED	-
RATED TORQUE	-
A.S.F.	-
COUPLING SPECIFICATIONS	
COUPLING RATING	6.5 KW @ 100 RPM
RATED TORQUE	621 Nm
MAX. BORE	48 mm
WEIGHT (Approx.)	6.206 kg
INERTIA (WK ²)	0.007 kg.M ²
TORSIONAL STIFFNESS	0.100 Nm/rod
CPLG DYNAMIC BALANCING TO GR 6.3 AS PER ISO 21940-11	
MAX. MISALIGNMENT	
AXIAL DEFLECTION	±1 mm
ANGULAR DEFLECTION	0.75°
RADIAL MISALIGNMENT	0.013mm

REV	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

NOTE:-

TIGHTENING TORQUE :-

1) SR.NO.8 COUPLING BOLT = 29Nm

2) SR.NO.7 ATTACHMENT BOLT = 29Nm

TITLE: REM-65(103)/I /XXXX CPLG

CUSTOMER NAME: RATHI TRANSPOWER PVT LTD PUNE-411014

MATERIAL: REFER TABLE

AUTHORITY INITIALS: SIGN DATE

SCALE: NTS

APPROVED: DRAWN CHECKED

REF. NO.: L/REM-XXXX/0