



DRIVE SIDE

DRIVEN SIDE

APPLICATION DETAILS

APPLICATION	-
RATED POWER	KW
RATED SPEED	RPM.
RATED TORQUE	Nm
A.S.F.	-

COUPLING CAPACITY

NORMAL TORQUE	160 Nm
MAXIMUM TORQUE	360 Nm
MAXIMUM BORE	42 mm.
WEIGHT (APPROX)	5.0 kg
INERTIA (WK ²)	0.003 kgm ²

COUPLING HUBS DYNAMICALLY BALANCED TO GR6.3 AS PER ISO 21940-11.

MAX. MISALIGNMENT

AXIAL	+0.61
ANGULAR	1'
PARALLEL	0.3

S.R.NO.	DESCRIPTION	MATERIAL	QTY.
3	SPIDER	NITRILE RUBBER	1
2	H TYPE HUB	C.I. GR FG.260	1
1	F TYPE HUB	C.I. GR FG.260	1

TITLE: **RFC-11F-H/- COUPLING**

CUSTOMER NAME: -

REV. DWG. NO.	DESCRIPTION	REV. BY	APPD. BY	DATE



RATHI TRANSPOWER PVT LTD
PUNE 411014

DRG. No.: -
SCALE: NTS/REF. No.: -

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions