



DRIVE SIDE
 M5X0.8P TAPPED HOLE
 FOR SET SCREW ON KEYWAY.

M5X0.8P TAPPED HOLE
 FOR SET SCREW ON KEYWAY.

DRIVEN SIDE

APPLICATION DETAILS

APPLICATION	-
RATED POWER	KW
RATED SPEED	RPM.
RATED TORQUE	Nm
A.S.F.	-

COUPLING CAPACITY

NORMAL TORQUE	160 Nm
MAXIMUM TORQUE	360 Nm
MAXIMUM BORE	55 mm.
WEIGHT ()	5.0 kg
INERTIA (WK ²)	0.003 kgm ²

COUPLING HUBS DYNAMICALLY BALANCED TO GR6.3 AS PER ISO 21940-11.

MAX. MISALIGNMENT

AXIAL	+0.61
ANGULAR	1'
PARALLEL	0.3

S.R.NO.	DESCRIPTION	MATERIAL	QTY.
3	SPIDER	NITRILE RUBBER	1
2	B TYPE HUB	C.I. GR FG.260	1
1	B TYPE HUB	C.I. GR FG.260	1

TITLE: **RFC-11B /----- COUPLING**

CUSTOMER NAME: -

REV. DWGN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE



RATHI TRANSPOWER PVT LTD
 PUNE 411014

DRG. No.: -----
 3 EN-F-112, REV.1