



DRIVE SIDE

M6X1P TAPPED HOLE FOR SET SCREW ON KEYWAY.

DRIVEN SIDE

M6X1P TAPPED HOLE FOR SET SCREW ON KEYWAY.

APPLICATION DETAILS

APPLICATION	-
RATED POWER	KW
RATED SPEED	RPM.
RATED TORQUE	Nm
A.S.F.	-

COUPLING CAPACITY

NORMAL TORQUE	950 Nm
MAXIMUM TORQUE	2350 Nm
MAXIMUM BORE	80 mm.
WEIGHT ()	18.2 kg
INERTIA (WK ²)	0.022 kgm ²

COUPLING HUBS DYNAMICALLY BALANCED TO GR6.3 AS PER ISO 21940-11.

MAX. MISALIGNMENT

AXIAL	+1.09
ANGULAR	1'
PARALLEL	0.4

S.R.NO.	DESCRIPTION	MATERIAL	QTY.
3	SPIDER	NITRILE RUBBER	1
2	B TYPE HUB	C.I. GR FG.260	1
1	B TYPE HUB	C.I. GR FG.260	1

TITLE: **RFC-18B /----- COUPLING**

CUSTOMER NAME: -

Lovejoy
RATHI TRANSPOWER PVT LTD
PUNE 411014

DRG. No.: -
3 EN-F-112, REV.1

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions