



**DRIVE SIDE**

M10X1.5P TAPPED HOLE  
FOR SET SCREW ON KEYWAY.

**DRIVEN SIDE**

M10X1.5P TAPPED HOLE  
FOR SET SCREW ON KEYWAY.

**APPLICATION DETAILS**

APPLICATION	-
RATED POWER	KW
RATED SPEED	RPM.
RATED TORQUE	Nm
A.S.F.	-

**COUPLING CAPACITY**

NORMAL TORQUE	2000 Nm
MAXIMUM TORQUE	5000 Nm
MAXIMUM BORE	100 mm.
WEIGHT ( )	35.0kg
INERTIA (WK <sup>2</sup> )	0.065 kgm <sup>2</sup>

COUPLING HUBS DYNAMICALLY BALANCED TO GR6.3 AS PER ISO 21940-11.

**MAX. MISALIGNMENT**

AXIAL	+1.32
ANGULAR	1'
PARALLEL	0.5

S.R.NO.	DESCRIPTION	MATERIAL	QTY.
3	SPIDER	NITRILE RUBBER	1
2	B TYPE HUB	C.I. GR FG.260	1
1	B TYPE HUB	C.I. GR FG.260	1

TITLE: **RFC-23B /----- COUPLING**

CUSTOMER NAME: -

REVISIONS:

REV.	DATE	BY	APPD.	DESCRIPTION

Lovejoy  
RATHI TRANSPOWER PVT LTD  
PUNE 411014

DRG. No.: -

3 EN-F-112, REV.1