



M10X1.5P TAPPED HOLE
FOR SET SCREW ON KEYWAY.

M10X1.5P TAPPED HOLE
FOR SET SCREW ON KEYWAY.

DRIVE SIDE

DRIVEN SIDE

APPLICATION DETAILS

APPLICATION	-
RATED POWER	KW
RATED SPEED	RPM.
RATED TORQUE	Nm
A.S.F.	-

COUPLING CAPACITY

NORMAL TORQUE	3150 Nm
MAXIMUM TORQUE	7200 Nm
MAXIMUM BORE	125 mm.
WEIGHT	68.7 kg
INERTIA	0.190 kgm ²

COUPLING HUBS DYNAMICALLY BALANCED TO GR6.3 AS PER ISO 21940-11.

MAX. MISALIGNMENT

AXIAL	+1.70
ANGULAR	1°
PARALLEL	0.5

S.R.NO.	DESCRIPTION	MATERIAL	QTY.
3	SPIDER	NITRILE RUBBER	1
2	B TYPE HUB	C.I. GR FG.260	1
1	B TYPE HUB	C.I. GR FG.260	1

TITLE: **RFC-28AB /----- COUPLING**

CUSTOMER NAME: -

REVISIONS:

REV.	DATE	BY	APPD. BY	DESCRIPTION

Lovejoy
RATHI TRANSPOWER PVT LTD
PUNE 411014

DRG. No.: -

3 EN-F-112, REV.1