



**DRIVE SIDE**

**DRIVEN SIDE**

M5X0.8P TAPPED HOLE  
FOR SET SCREW ON KEYWAY.

M5X0.8P TAPPED HOLE  
FOR SET SCREW ON KEYWAY.

**APPLICATION DETAILS**

APPLICATION	-
RATED POWER	KW
RATED SPEED	RPM.
RATED TORQUE	Nm
A.S.F.	-

**COUPLING CAPACITY**

NORMAL TORQUE	31.5 Nm
MAXIMUM TORQUE	72 Nm
MAXIMUM BORE	32 mm.
WEIGHT ( )	1.1kg
INERTIA (WK <sup>2</sup> )	0.0003kgm <sup>2</sup>

COUPLING HUBS DYNAMICALLY BALANCED TO GR6.3 AS PER ISO 21940-11.

**MAX. MISALIGNMENT**

AXIAL	+0.2
ANGULAR	1'
PARALLEL	0.3

S.R.NO.	DESCRIPTION	MATERIAL	QTY.
3	SPIDER	NITRILE RUBBER	1
2	B TYPE HUB	C.I. GR FG.260	1
1	B TYPE HUB	C.I. GR FG.260	1

TITLE:	RFC-7B/----- COUPLING								
CUSTOMER NAME:	-								
REVISIONS:	<table border="1"> <tr> <th>NO.</th> <th>DATE</th> <th>BY</th> <th>REASON</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table>	NO.	DATE	BY	REASON				
NO.	DATE	BY	REASON						

**RATHI TRANSPOWER PVT LTD**  
 PUNE 411014  
 DRG. No.: -----  
 SCALE: NTS/REF: No.: -----  
 APPROVED: \_\_\_\_\_  
 CHECKED: \_\_\_\_\_  
 DRAWN: \_\_\_\_\_  
 AUTHORITY INITIALS: \_\_\_\_\_ SIGN: \_\_\_\_\_ DATE: \_\_\_\_\_

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions