



DRIVE SIDE

DRIVEN SIDE

APPLICATION DETAILS

APPLICATION	-
RATED POWER	KW
RATED SPEED	RPM.
RATED TORQUE	Nm
A.S.F.	-

COUPLING CAPACITY

NORMAL TORQUE	80 Nm
MAXIMUM TORQUE	180 Nm
MAXIMUM BORE	28 mm.
WEIGHT (APPROX.)	1.8kg
INERTIA (WK ²)	0.001 kgm ²

COUPLING HUBS DYNAMICALLY BALANCED TO GR6.3 AS PER ISO 21940-11.

MAX. MISALIGNMENT

AXIAL	+0.49
ANGULAR	1'
PARALLEL	0.3

S.R.NO.	DESCRIPTION	MATERIAL	QTY.
3	SPIDER	NITRILE RUBBER	1
2	H TYPE HUB	C.I. GR FG.260	1
1	F TYPE HUB	C.I. GR FG.260	1

TITLE: **RRC-9F-H / - - - - COUPLING**

CUSTOMER NAME: -

REV. DWGN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE



RATHI TRANSPOWER PVT LTD
PUNE 411014

DRG. No.: - - - - - / -
3 EN-F-112, REV.1