



DRIVE SIDE
 M5X0.8P TAPPED HOLE
 FOR SET SCREW ON KEYWAY.

DRIVEN SIDE

APPLICATION DETAILS

APPLICATION	-
RATED POWER	KW
RATED SPEED	RPM.
RATED TORQUE	Nm
A.S.F.	-

COUPLING CAPACITY

NORMAL TORQUE	80 Nm
MAXIMUM TORQUE	180 Nm
MAXIMUM BORE	42 mm.
WEIGHT ()	1.8kg
INERTIA (WK ²)	0.001 kgm ²

COUPLING HUBS DYNAMICALLY BALANCED TO GR6.3 AS PER ISO 21940-11.

MAX. MISALIGNMENT

AXIAL	+0.49
ANGULAR	1'
PARALLEL	0.3

S.R.NO.	DESCRIPTION	MATERIAL	QTY.
3	SPIDER	NITRILE RUBBER	1
2	B TYPE HUB	C.I. GR FG.260	1
1	B TYPE HUB	C.I. GR FG.260	1

TITLE: **RFC-9B/----- COUPLING**

CUSTOMER NAME: -

REVISIONS:

REV.	DATE	BY	APPD.

Lovejoy
 RATHI TRANSPOWER PVT LTD
 PUNE 411014

DRG. No.: -

3 EN-F-112, REV.1