



**APPLICATION DETAILS**

APPLICATION	-
RATED POWER	-
RATED SPEED	-
RATED TORQUE	-
A.S.F.	-

**COUPLING SPECIFICATION**

COUPLING RATING	336 kW @ 100 RPM
RATED TORQUE	32.086 kNm.
PEAK TORQUE	64.172 kNm
MAX. SPEED	3600 rpm
MAX. BORE	160 mm
INERTIA(WK <sup>2</sup> )	0.961 Kgm <sup>2</sup>
WEIGHT(Approx.)	100 kg

ONLY OPLG HUBS TO BE DYNAMICALLY BALANCED TO Gr. 6.3; ISO-21940-11

**MAX. MISALIGNMENTS**

AXIAL DEFLECTION	±1 mm
ANGULAR DEFLECTION	±1.5° Deg./Gear mesh
RADIAL DEFLECTION	2 mm

**NOTE:-**  
 \* GREASE PLUG ON BOTH SLEEVES WILL BE PROVIDED FOR LUBRICATION.  
 \* TIGHTENING TORQUE OF THE BOLT(S.NO.-3) - 167 Nm  
 \* GREASE QTY. - 0.79 Kg (CUSTOMER'S SCOPE)

S.R.NO.	DESCRIPTION	MATERIAL	QTY
7	'O' RING	NITRILE RUBBER	2
6	HEX NUT	GR 8.0 (MIN)	8
5	SPRING WASHER	SPRING STEEL	8
4	GASKET	NON ASBESTOS PAPER	1
3	HEX HEAD BOLT	GR 8.8	8
2	SLEEVE	C55 BS EN 10277-2	2
1	HUB	C55 BS EN 10277-2	2

TITLE:	<b>RGD-40 / - COUPLING</b>
CUSTOMER NAME:	<b>RATHI TRANSPOWER PVT LTD</b>
DRWN	-
CHECKED	-
APPROVED	-
SCALE: NTS/REF. No.:	-
AUTHORITY INITIALS	-
SIGN	-
DATE	-

REV. DWRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

**Lovefox** RATHI TRANSPOWER PVT LTD PUNE 411014 DRG. No.: -

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions