IF IN DOUBT, PLEASE ASK | DO NOT SCALE | ALL DIMENSIONS ARE IN mm



DRIVE SIDE





DRIVEN SIDE

APPLICATION DETAILS	
APPLICATION	–
RATED POWER	– KW
RATED SPEED	– RPM
RATED TORQUE	– kNm
A.S.F	–
COUPLING SPECIFICATIONS	
COUPLING RATING	0.65kW @ 100 RPM
RATED TORQUE	62Nm
MAX BORE TYPE–I&II	24mm & 28mm
WEIGHT (APPROX)	0.34 Kg
INERTIA WK^2 (APPROX)	$19X10^{-5}$ kg–m^2
CPLG COMPONENTS DYNAMICALLY BALANCED TO GR.6.3 AS PER ISO 21940–II.	
MAXIMUM MISALIGNMENTS	
AXIAL DEFLECTION	±1.6 mm
ANGUALR DEFLECTION	0.80°
RADIAL DEFLECTION	0.15 mm

SR NO	DESCRIPTION	MATERIAL	QTY.
3	HUB–II	LM24	1
2	SPIDER	POLYURETHANE (BLUE)	1
1	HUB–I	LM24	1

REV.	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

TITLE: RRJ–24 I/II /---- CPLG.

MATERIAL: REFER TABLE

AUTHORITY	INITIALS	SIGN	DATE
DRAWN	–		–
CHECKED	–		–
APPROVED	–		–

SCALE: NTS | REF. No.:

CUSTOMER NAME: -

Lovejoy INDIA

RATHI TRANSPOWER PVT LTD
PUNE 411014

DRG. No.: -----/–

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions

– 0/

3 EN–F–112