



DRIVEN SIDE

DRIVE SIDE

(REF.)

(DBSE)

(DBSE)

(REF.)

(REF.)

**APPLICATION DETAILS**

APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM.
RATED TORQUE	- Nm
A.S.F.	-

**COUPLING CAPACITY**

COUPLING RATING	4.21KW AT 100RPM.
RATED TORQUE	402Nm
MAX. BORE TYPE-I	40mm
WEIGHT (APPROX)	2.0kg
INERTIA (WK <sup>2</sup> )	1.85X10 <sup>-3</sup> kg-m <sup>2</sup>

**MAX. MISALIGNMENT**

AXIAL	±2.2mm
ANGULAR	0.9°
PARALLE	0.25mm

SER NO	DESCRIPTION	MATERIAL	QTY.
3	HUB-I	C:1 GR FG 260	1
2	SPIDER	POLYURETHANE (LIGHT WORN)	1
1	HUB-I	C:1 GR FG 260	1

TITLE: **RRJ-38 I/1 /- - - -**  
 CPLG.  
 CUSTOMER NAME: -  
 MATERIAL: **REFER TABLE**  
 AUTHORITY INITIALS: -  
 SIGN: -  
 DATE: -  
 DRAWN: -  
 CHECKED: -  
 APPROVED: -  
 SCALE: N/S REF. No.: -

REV. DMRN NO. DESCRIPTION REV. BY APPD. BY DATE  
 RATHI TRANSPOWER PVT. LTD  
 PUNE 411006  
 DRG No.: **R/L- - - - / -**  
 3 EN-F-112

