



APPLICATION DETAILS

APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM.
RATED TORQUE	- Nm
A.S.F.	-

COUPLING CAPACITY

COUPLING RATING	4.99KW AT 100RPM.
RATED TORQUE	4.77Nm
MAX. BORE TYPE-I & II	45 & 55mm
WEIGHT (APPROX)	3.8kg
INERTIA (WK ²)	5.9X10 ⁻³ kg-m ²

MAX. MISALIGNMENT

AXIAL	± 2.3 mm
ANGULAR	0.90°
PARALLEL	0.30mm

SERIAL NO.	DESCRIPTION	MATERIAL	QTY.
3	HUB-II	C.I. IS:210 FG 260	1
2	SPIDER	POLYURETHANE (BLUE)	1
1	HUB-I	C.I. IS:210 FG 260	1

TITLE: **RRJ-42 I/II /-----**

CUSTOMER NAME: **RATHI TRANSPOWER PVT LTD**

REFER TABLE

AUTHORITY INITIALS | SIGN | DATE

DRAWN | CHECKED | APPROVED

SCALE: N/S REF. No.:

REV. DMRN NO. | DESCRIPTION | REV. BY | APPD. BY | DATE

DRG. No.:

3 EN-F-112