



APPLICATION DETAILS	
APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM.
RATED TORQUE	- Nm
A.S.F.	-
COUPLING CAPACITY	
COUPLING RATING	4.99KW AT 100RPM.
RATED TORQUE	477 Nm
MAX. BORE TYPE-III	55mm
WEIGHT (APPROX)	5.5kg
INERTIA (WK ²)	8.54X10 ⁻³ kg-m ²
MAX. MISALIGNMENT	
AXIAL	±2.3mm
ANGULAR	0.90°
PARALLE	0.30mm

SR NO	DESCRIPTION	MATERIAL	QTY.
3	HUB-III	C.I. IS:210 FG 260	1
2	SPIDER	POLYURETHANE (BLUE)	1
1	HUB-III	C.I. IS:210 FG 260	1

REV.	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

TITLE: **RRJ-42 III/III /-----**
CPLG.

MATERIAL: **REFER TABLE**

CUSTOMER NAME: -

AUTHORITY	INITIALS	SIGN	DATE
DRAWN	-	-	-
CHECKED	-	-	-
APPROVED	-	-	-

SCALE: NTS REF. No.: -

DRG. No.: -----/-

Lovejoy RATHI TRANSPower PVT LTD PUNE 411014

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions