



**APPLICATION DETAILS**

APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM
RATED TORQUE	- Nm
A.S.F.	-

**COUPLING CAPACITY**

COUPLING RATING	6.98KW AT 100RPM.
RATED TORQUE	667Nm
MAX. BORE TYPE-I & II	52 & 62mm
WEIGHT (APPROX)	5.2kg
INERTIA (WK <sup>2</sup> )	9.6X10 <sup>-3</sup> kg-m <sup>2</sup>

**MAX. MISALIGNMENT**

AXIAL	±3.0mm
ANGULAR	1°
PARALLEL	0.35mm

REV	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

TITLE: **RRJ-48 I/II /----- CPLG.**

CUSTOMER NAME: -

SERIAL NO	DESCRIPTION	MATERIAL	QTY.
3	HUB-II	C.I. IS:210 FG 260	1
2	SPIDER	POLYURETHANE (LIGHT WORY)	1
1	HUB-I	C.I. IS:210 FG 260	1

**REFER TABLE**

AUTHORITY INITIALS	SIGN	DATE
DRAWN	-	-
CHECKED	-	-
APPROVED	-	-

SCALE: NTS REF. No.: -

DRG. No.: -----/

**Lovejoy** **RATHI TRANSPOWER PVT LTD** **PUNE 411014**