



M5X0.8P TAPPED HOLE FOR SET SCREW ON KEYWAY.

M5X0.8P TAPPED HOLE FOR SET SCREW ON KEYWAY.

**DRIVE SIDE**

**DRIVEN SIDE**

APPLICATION DETAILS	
APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM.
RATED TORQUE	- Nm
A.S.F.	-
COUPLING CAPACITY	
COUPLING RATING	3.1KW AT 100RPM.
RATED TORQUE	296 Nm
MAX. BORE TYPE-III	62mm
WEIGHT (APPROX)	4.2kg
INERTIA (WK <sup>2</sup> )	13.4X10 <sup>-3</sup> kg-m <sup>2</sup>
MAX. MISALIGNMENT	
AXIAL	±3.0mm
ANGULAR	1°
PARALLE	0.35mm

SR NO	DESCRIPTION	MATERIAL	QTY.
3	HUB-III	C.I. IS:210 FG 260	1
2	SPIDER	POLYURETHANE (GRAY)	1
1	HUB-III	C.I. IS:210 FG 260	1

REV.	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

TITLE: <b>RRJ-48 III/III /----</b>		MATERIAL: <b>REFER TABLE</b>		AUTHORITY	INITIALS	SIGN	DATE
CUSTOMER NAME: -		SCALE: NTS REF. No.:		DRAWN	-	-	-
				CHECKED	-	-	-
				APPROVED	-	-	-
				DRG. No.:		-----/-	
				RATHI TRANSPOWER PVT LTD		PUNE 411014	

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions