IF IN DOUBT, PLEASE ASK		DO NOT SCALE	ALL DIMENSIONS ARE IN mm

J I H G F E D C B A

8 7 6 5 4 3 2 1



DRIVE SIDE

DRIVEN SIDE

APPLICATION DETAILS	
APPLICATION	–
RATED POWER	– KW
RATED SPEED	– RPM
RATED TORQUE	– kNm
A.S.F	–
COUPLING SPECIFICATIONS	
COUPLING RATING	0.33 KW AT 100 RPM.
RATED TORQUE	31.7 Nm
MAX.BORE	28 mm.
WEIGHT(Approx.)	1.1 Kg
INERTIA WK^2	0.00045 Kgm^2
COUPLING HUBS DYNAMICALLY BALANCED TO GR6.3 AS PER ISO 21940–11.	
MAX. MISALIGNMENTS	
AXIAL DEFLECTION	±1 mm
ANGUALR DEFLECTION	1°
RADIAL DEFLECTION	0.4mm

ITEM NO.	DESCRIPTION	MATERIAL	QTY.
6	HUB DRIVEN SIDE	C.I. GR.FG 260	1
5	OUTSIDE RING BOLT	CH SCREW–SS	6
4	OUTSIDE RING	C.R.C.A	2
3	SNAP WRAP	POLYURETHANE RUBBER	2
2	SPACER	LM24	1
1	HUB DRIVE SIDE	C.I. GR.FG 260	1

REV.	DMRN NO.	DESCRIPTION	REV. BY	APPD. BY	DATE

TITLE: **RRS–095 (90)/–CPLG.**

MATERIAL: **REFER TABLE**

CUSTOMER NAME: -

AUTHORITY	INITIALS	SIGN	DATE
DRAWN	–		–
CHECKED	–		–
APPROVED	–		–

SCALE: NTS REF. No.:

Lovejoy INDIA

RATHI TRANSPOWER PVT LTD
PUNE 411014

DRG. No.: ----/-

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions