



APPLICATION DETAILS

APPLICATION	-
RATED POWER	- KW
RATED SPEED	- RPM
RATED TORQUE	- Nm
A.S.F.	-

COUPLING SPECIFICATIONS

COUPLING RATING	0.33 KW AT 100 RPM
RATED TORQUE	31.70 Nm
MAX. BORE	28 mm
WEIGHT (Approx.)	0.80 Kg
INERTIA (WK ²)	3.67x10 ⁻⁴ Kgm ²

CPLG. HUBS DYNAMICALLY BALANCED TO GR.6.3 AS PER ISO 21940-11.

MAX. MISALIGNMENTS

AXIAL DEFLECTION	±1 mm
ANGULAR DEFLECTION	1°
RADIAL DEFLECTION	0.4 mm

SR NO	DESCRIPTION	MATERIAL	QTY.
4	OUTSIDE RING BOLT	CH SCREW-SS	3
3	OUTSIDE RING	CRCA	1
2	SNAP WRAP	POLYURETHANE	1
1	HUB	CI GR FG 260	2

TITLE:	SW-95/-----CPLG	REFER TABLE
CUSTOMER NAME:	RATHI TRANSPOWER PVT LTD PUNE 411006	
AUTHORITY:	INITIALS	SIGN
DRAWN	-	-
CHECKED	-	-
APPROVED	-	-
SCALE:	REF. No.:	DATE

REV. / DIM. NO.	DESCRIPTION	REV. BY	DATE

This drawing / information / design is the property of Rathi Transpower Pvt. Ltd. It is confidential & must not be made public or copied without prior written authorization & is subjected to recall at any time. Acceptance of this drawing constitutes full agreement with these conditions