



APPLICATION DETAILS	
APPLICATION	-
RATED POWER	-
RATED SPEED	-
RATED TORQUE	-
A.S.F.	-

COUPLING SPECIFICATIONS	
COUPLING RATING	7.07 kW @ 100 RPM
RATED TORQUE	0.67 kNm.
PEAK TORQUE	1.35 kNm.
MAX. SPEED	2600 rpm.
MAX. BORE	80 mm
WEIGHT(Approx.)	20.7 Kg
INERTIA (WK ²)	0.125 kgm ²
COUPLING HUBS DYNAMICALLY BALANCED TO GR.6.3 AS PER ISO: 1940-1.	

SR NO	DESCRIPTION	MATERIAL	QTY.
1	HUB	CI IS-210 GR.FG 260	2
2	TYRE	NATURAL RUBBER	1
3	CLAMPING RING	S.G. IRON-400/15	2
4	HEX HEAD BOLT	HIGH TENSILE STEEL	12
5	SPRING WASHER	SPRING STEEL	12

TITLE: **70-10 B /----- CPLG.**

CUSTOMER NAME: **RATHI TRANSPOWER PVT LTD**

REVISIONS:

REV.	DATE	DESCRIPTION

APPROVED:

SCALE: NTS REF. No. 1

DRG. No.: -----